NSN 5962-01-139-2440

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-139-2440 **Body Length:** Between 0.740 inches and 0.760 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.160 inches **Maximum Power Dissipation Rating:** 670.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4920-01-046-1830 18323 **Features Provided:** W/common mode and w/strobe and w/resistor and w/active pull-up and positive outputs **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 5 input **Design Function And Quantity:** 2 receiver, line differential **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0