NSN 5962-01-139-3614

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-139-3614

Body Length: Between 0.745 inches and 0.770 inches Body Width: Between 0.240 inches and 0.260 inches Body Height: Between 0.065 inches and 0.140 inches Maximum Power Dissipation Rating:
Body Width: Between 0.240 inches and 0.260 inches Body Height: Between 0.065 inches and 0.140 inches Maximum Power Dissipation Rating:
Between 0.240 inches and 0.260 inches Body Height: Between 0.065 inches and 0.140 inches Maximum Power Dissipation Rating:
Body Height: Between 0.065 inches and 0.140 inches Maximum Power Dissipation Rating:
Between 0.065 inches and 0.140 inches Maximum Power Dissipation Rating:
Maximum Power Dissipation Rating:
200.0 1111 11
500.0 milliwatts
Operating Tempurature Range:
55.0/+125.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
End Application:
An/grc-212 13499
Features Provided:
Hermetically sealed and monolithic and w/clock and w/reset
nclosure Material:
Ceramic and glass
nclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
nput Circuit Pattern:
Dual 4 input
Fime Rating Per Chacteristic:
200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level
putput
Shelf Life:
N/a
Jnit Of Measure:
-
Demilitarization:
Yes - demil/mli
Filg:
A458a0