NSN 5962-01-139-5789

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-139-5789 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** An/sqs-53aec6 e/i fscm 03538 **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs and electrostatic sensitive **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 2 switch, analog **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 17.0 volts power source **Test Data Document:** 03538-7846258+001 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-139-5789

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0