

View Online at <https://aerobasegroup.com/nsn/5962-01-140-9543>

**Body Length:**

0.840 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

400.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Offavionics/c 82918; support equipment, mx peacekeeper missile; ticonderoga class cg (47); los angeles class ssn (688); virginia class cgn (41); low altitude navigation & targeting infrared system (lantirn); tactical data system, an/uva- (v); over the horizon back scanner (oth-b) program (an/fps-118); missile, air-to-air, phoenix (aim-54); central office, telephone auto; spruance class dd (963)

**Features Provided:**

Hermetically sealed and monolithic and high speed and w/enable

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Input Circuit Pattern:**

2 input

**Criticality Code Justification:**

Feat

**Design Function And Quantity:**

1 comparator, voltage

**Case Outline Source And Designator:**

D-2 mil-m-38510

**Current Rating Per Characteristic:**

10.00 milliamperes output

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

4.0 volts power source

**Time Rating Per Characteristic:**

15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

**Special Features:**

Weapon system essential

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

16 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A458a0