

View Online at <https://aerobasegroup.com/nsn/5962-01-141-4885>

Body Length:

0.870 inches

Body Width:

Between 0.220 inches and 0.280 inches

Body Height:

0.180 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Harpoon msl t 76301

Features Provided:

Hermetically sealed and w/strobe and high fan-out and low impedance and w/totem pole output

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 6 input

Design Function And Quantity:

2 selector, data, four to one line

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

5.5 volts power source

Time Rating Per Characteristic:

34.00 nanoseconds propagation delay time, low to high level output and 34.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

30003-642as2710 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0