NSN 5962-01-141-5678

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-141-5678

| Body Length: |
|--|
| Between 1.248 inches and 1.256 inches |
| Body Width: |
| 0.700 inches |
| Body Height: |
| Between 0.250 inches and 0.340 inches |
| Maximum Power Dissipation Rating: |
| 3000.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+175.0 degrees celsius |
| End Application: |
| Bomb dir radr 12115 |
| Features Provided: |
| Hermetically sealed and monolithic and high current and high power |
| Inclosure Material: |
| Metal |
| Inclosure Configuration: |
| Can |
| Input Circuit Pattern: |
| 3 input |
| Design Function And Quantity: |
| 1 driver, switch |
| Case Outline Source And Designator: |
| T0-66 joint electron device engineering council |
| Terminal Surface Treatment: |
| Tin |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |