# NSN 5962-01-141-5689

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-141-5689 **Body Length:** Between 1.180 inches and 1.220 inches **Body Width:** Between 0.585 inches and 0.615 inches **Body Height:** Between 0.060 inches and 0.105 inches **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius **End Application:** 4920-01-084-7157 e/i fscm 26916 **Features Provided:** Hermetically sealed and monolithic and positive outputs and programmable and 3-state output **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 12 input

#### **Terminal Surface Treatment:**

Solder

#### **Voltage Rating And Type Per Characteristic:**

-0.3 volts power source and 15.0 volts power source

#### **Time Rating Per Chacteristic:**

550.00 nanoseconds propagation delay time, low to high level output and 550.00 nanoseconds propagation delay time, high to low level output

#### **Memory Device Type:**

Rom

## **Memory Capacity:**

Unknown

#### **Test Data Document:**

28480-1818-0364 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### **Terminal Type And Quantity:**

24 printed circuit

### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-141-5689

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0