# NSN 5962-01-142-5123

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-142-5123

# Body Length: 1.230 inches

# **Body Width:**

Between 0.580 inches and 0.620 inches

# **Body Height:**

Between 0.150 inches and 0.180 inches

# **Maximum Power Dissipation Rating:**

1.0 watts

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

# Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

Spectrum anal 28480

#### Features Provided:

Hermetically sealed and 3-state output and high performance and low power and programmed and high impedance and wire-or outputs

#### **Inclosure Material:**

Ceramic and glass

# Inclosure Configuration:

Dual-in-line

# Output Logic Form:

N-type metal oxide-semiconductor logic

#### Input Circuit Pattern:

14 input

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

#### Time Rating Per Chacteristic:

350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output

# Memory Device Type:

Rom

# Memory Capacity:

Unknown

# **Terminal Type And Quantity:**

24 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

---

### Demilitarization:

Yes - demil/mli

# NSN 5962-01-142-5123

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

