NSN 5962-01-142-5124



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-142-5124 **Body Length:** 1.230 inches **Body Width:** Between 0.580 inches and 0.620 inches **Body Height:** Between 0.150 inches and 0.180 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Spectrum anal 28480 **Features Provided:** Hermetically sealed and 3-state output and high performance and low power and programmed and high impedance and wire-or outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 14 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Terminal Type And Quantity:** 24 printed circuit Shelf Life:

Demilitarization: Yes - demil/mli

Unit Of Measure:

N/a

NSN 5962-01-142-5124

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0