### NSN 5962-01-142-7327

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-142-7327

# Body Length:

1.230 inches

### Body Width:

Between 0.580 inches and 0.620 inches

#### **Body Height:**

Between 0.150 inches and 0.180 inches

#### **Maximum Power Dissipation Rating:**

1.0 watts

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

Spectrum anal 28480

#### Features Provided:

Hermetically sealed and 3-state output and high performance and low power and programmed and high impedance and wire-or outputs

#### **Inclosure Material:**

Ceramic and glass

#### Inclosure Configuration:

Dual-in-line

#### Output Logic Form:

N-type metal oxide-semiconductor logic

#### Input Circuit Pattern:

14 input

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

7.0 volts power source

#### Time Rating Per Chacteristic:

350.00 nanoseconds propagation delay time, low to high level output and 350.00 nanoseconds propagation delay time, high to low level output

#### Memory Device Type:

Rom

#### Memory Capacity:

Unknown

#### **Terminal Type And Quantity:**

24 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

## NSN 5962-01-142-7327

Memory Microcircuit - Page 2 of 2

**Fiig:** A458a0

