

View Online at <https://aerobasegroup.com/nsn/5962-01-144-8986>

**Body Length:**

Between 1.185 inches and 1.215 inches

**Body Width:**

Between 0.570 inches and 0.605 inches

**Body Height:**

0.145 inches

**Maximum Power Dissipation Rating:**

525.0 milliwatts

**Operating Temperature Range:**

+0.0/+70.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**End Application:**

Anadigtester e/i fscm 88818

**Features Provided:**

Hermetically sealed and monolithic and positive outputs and electrostatic sensitive and erasable and low power and programmable and programmed

**Inclosure Material:**

Ceramic and glass

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

N-type metal oxide-semiconductor logic

**Input Circuit Pattern:**

12 input

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.3 volts power source and 6.0 volts power source

**Time Rating Per Characteristic:**

450.00 nanoseconds propagation delay time, low to high level output and 450.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Prom

**Memory Capacity:**

Unknown

**Test Data Document:**

88818-a398a033t1011 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0