## NSN 5962-01-144-9299



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-144-9299 **Body Length:** 0.785 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4920-01-121-0603 fscm 77272 **Features Provided:** Hermetically sealed and monolithic and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, nand **Case Outline Source And Designator:** D-1 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 18.5 volts power source **Time Rating Per Chacteristic:** 

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

### **Test Data Document:**

94580-10063964 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

#### **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-144-9299

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0