NSN 5962-01-146-2015



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-146-2015 **Body Length:** 0.870 inches **Body Width:** 0.250 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 127.0 milliwatts **Operating Tempurature Range:** -0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 2f92a tactics 20551 **Features Provided:** Monolithic and positive edge triggered and w/common clear **Inclosure Material:** Plastic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Quad 3 input **Design Function And Quantity:** 4 flip-flop, d-type **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 5.5 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 20551-a380 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli

Demilitarization:

NSN 5962-01-146-2015

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0