NSN 5962-01-146-2105

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-146-2105 **Body Length:** 0.800 inches **Body Width:** 0.288 inches **Body Height:** 0.095 inches **Maximum Power Dissipation Rating:** 1.25 watts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4920-01-049-0223 e/i fscm 88818 **Features Provided:** Hermetically sealed and monolithic and positive outputs and 3-state output and expandable **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 20.0 volts power source **Time Rating Per Chacteristic:** 375.00 nanoseconds propagation delay time, low to high level output and 375.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Ram **Memory Capacity:** Unknown **Test Data Document:** 28480-1818-0334 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

--

N/a

Terminal Type And Quantity:

16 printed circuit

Unit Of Measure:

Shelf Life:

NSN 5962-01-146-2105

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0