NSN 5962-01-146-6600

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/psn/5062-01-146-6600

| View Online at https://aerobasegroup.com/nsn/5962-01-146-6600 |
|---|
| Body Length: |
| Between 1.695 inches and 1.705 inches |
| Body Width: |
| Between 0.770 inches and 0.780 inches |
| Body Height: |
| 0.210 inches |
| Operating Tempurature Range: |
| -55.0 to 125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0 to 135.0 degrees celsius |
| Features Provided: |
| Hybrid and hermetically sealed |
| Inclosure Material: |
| Ceramic or glass or metal |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| Transistor-transistor logic |
| Input Circuit Pattern: |
| 3 input |
| Design Function And Quantity: |
| 1 converter, synchro to digital |
| Terminal Surface Treatment: |
| Gold |
| Voltage Rating And Type Per Characteristic: |
| -18.0 volts power source and 18.0 volts power source |
| Precious Material And Location: |
| Terminal surfaces gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 09344-pc73525 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Terminal Type And Quantity: |
| 36 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

Fiig:

A458a0

Yes - demil/mli