NSN 5962-01-146-9136

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-01-146-9136
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Body Height:
Between 0.165 inches and 0.185 inches
Maximum Power Dissipation Rating:
450.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
1240-01-096-5151 19207
Features Provided:
Hermetically sealed and negative outputs and positive outputs
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
1 input
Design Function And Quantity:
1 switch, analog, single pole double throw
Case Outline Source And Designator:
A-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
32.0 volts power source
Time Rating Per Chacteristic:
250.00 nanoseconds propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level output and 150.00 nanoseconds.
output
Test Data Document:
19207-12293385 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
10 pin
Shelf Life:
N/a
Unit Of Measure:
_

Fiig: A458a0

Demilitarization: Yes - demil/mli