NSN 5962-01-147-3047

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-147-3047 **Body Length:** Between 0.750 inches and 0.770 inches **Body Width:** Between 0.275 inches and 0.290 inches **Body Height:** 0.199 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** An/wlr-6 33472 **Features Provided:** Monolithic and hermetically sealed and asynchronous and expandable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Metal oxide-semiconductor logic **Input Circuit Pattern:** 6 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -20.0 volts power source and 0.3 volts power source **Memory Device Type:** First-in first-out **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

NSN 5962-01-147-3047

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0