NSN 5962-01-147-3927

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-147-3927
Body Length:
Between 0.370 inches and 0.434 inches
Body Width:
Between 0.240 inches and 0.285 inches
Body Height:
Between 0.030 inches and 0.090 inches
Maximum Power Dissipation Rating:
660.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Computer 97384
Features Provided:
Hermetically sealed and burn in and bipolar and 3-state output and w/totem pole output and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
6 input
Design Function And Quantity:
4 register, d-type
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-1.2 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
9.00 nanoseconds propagation delay time, low to high level output and 13.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
27963-85938900 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
16 flat leads
Shelf Life:
N/a
Unit Of Measure:

Yes - demil/mli

Demilitarization:

NSN 5962-01-147-3927

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0