## NSN 5962-01-148-9244

Linear Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/hsn/5962-01-146-9244               |
|---|
| Body Length:  |
| Between 0.660 inches and 0.785 inches                                       |
| Body Width:   |
| Between 0.220 inches and 0.280 inches                                       |
| Body Height:  |
| 0.180 inches  |
| Maximum Power Dissipation Rating:   |
| 670.0 milliwatts  |
| Operating Tempurature Range:  |
| +0.0/+70.0 degrees celsius  |
| Storage Tempurature Range:  |
| -65.0/+150.0 degrees celsius  |
| End Application:  |
| 5820-01-092-0435 receiver, radio  |
| Features Provided:  |
| Gain controlled and high performance and monolithic and hermetically sealed |
| Inclosure Material:   |
| Ceramic and glass   |
| Inclosure Configuration:  |
| Dual-in-line  |
| Input Circuit Pattern:  |
| 5 input   |
| Design Function And Quantity:   |
| 1 amplifier, intermediate frequency   |
| Case Outline Source And Designator:   |
| T0-116 joint electron device engineering council                            |
| Terminal Surface Treatment:   |
| Solder  |
| Voltage Rating And Type Per Characteristic:                                 |
| 15.0 volts power source   |
| Terminal Type And Quantity:   |
| 14 printed circuit  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| Yes - demil/mli   |
|   |

Fiig:

A458a0