NSN 5962-01-149-2318

Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-149-2318

Diverall Height: 1.425 inches Diverall Width: 1.650 inches 3.60dy Length: 1.290 inches 3.60dy Length: 1.290 inches 3.60dy Length: 1.290 inches 3.60dy Height: 1.292 inches 3.60dy Height: 1.292 inches 3.60dy Height: 1.292 inches 3.60dy Height: 1.292 inches Diverating Tempurature Range: 5.5, 10 125,0 degrees celsius Features Provided: 3.610 inches 3.610 inc	
Overall Height: 0.425 inches Overall Width: 0.650 inches 30dy Length: 1.290 inches 30dy Width: 0.610 inches 30dy Height: 0.225 inches Operating Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: 31jolar and burn in, mil-sid-883, class a and monolithic nolosure Configuration: Flat pack Case Outline Source And Designator: Fry-02 mill-m-38510 Fest Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, stac; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813867 drawing (this is the dasic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813827 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governi	Overall Length:
Devail Width: .050 inches .030dy Length: .050 inches .030dy Width: .0510 inches .050dy Height: .0510 inches .050dy Height: .055.0 to 125.0 degrees celsius .055.0 to 125.0 degrees celsius .0510 and burn in, mil-std-883, class a and monolithic .0510 inclosure Configuration: .0510 and Designator: .0510 and De	1.290 inches
Overall Width: 0.650 inches 30dy Length: 1.290 inches 30dy Width: 1.610 inches 30dy Height: 1.225 inches 30dy Height: 1.225 inches 30dy Eleight: 1.225 inches 30dy Eleight: 31polar and burn in, mil-std-883, class a and monolithic 1.226 inches 31polar and burn in, mil-std-883, class a and monolithic 1.226 inches 32polar and burn in, mil-std-883, class a and monolithic 1.226 inches 32polar and burn in, mil-std-883, class a and monolithic 1.226 inches 32polar and burn in, mil-std-883, class a and monolithic 1.227 inches 32polar and burn in, mil-std-883, class a and monolithic 1.228 inches 32polar and burn in, mil-std-883, class a and monolithic 1.229 inches 32polar and burn in, mil-std-883, class a and monolithic 1.229 inches 32polar and burn in, mil-std-883, class a and monolithic 1.229 inches 32polar and burn in, mil-std-883, class a and monolithic 1.239 inches 2.240 inches 2.250 i	Overall Height:
Body Length: 1.290 inches 30dy Width: 1.290 inches 30dy Width: 1.291 inches 30dy Height: 1.225 inches Departing Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: 31polar and burn in, mil-std-883, class a and monolithic Inclosure Configuration: 1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-1-	0.425 inches
Body Length: 1.290 inches Body Width: 1.610 inches Body Width: 1.620 inches Body Height: 1.225 inches Deperating Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in, mil-std-883, class a and monolithic Inclosure Configuration: Flat pack Case Outline Source And Designator: Fly-02 mil-m-38510 Fest Data Document: 100063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, stc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Via Unit Of Measure: - Demilitarization: No	Overall Width:
1.290 inches 30dy Width: 0.610 inches 30dy Height: 0.225 inches 0.225 inches 0.255.0 to 125.0 degrees celsius 6-6atures Provided: 3ipolar and burn in, mil-std-883, class a and monolithic nclosure Configuration: Flat pack 2-6ase Outline Source And Designator: Fly-02 mil-m-38510 Fest Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, atc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing).	0.650 inches
Sody Width: 0.610 inches Body Height: 0.225 inches Deparating Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in, mil-std-883, class a and monolithic Inclosure Configuration: Flat pack Case Outline Source And Designator: Fly-02 mil-m-38510 Fest Data Document: 80063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: V/a Jnit Of Measure: Demilitarization:	Body Length:
Body Height: Departing Tempurature Range: 5.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in mil-std-883, class a and monolithic noclosure Configuration: Flat pack Case Outline Source And Designator: Fly-02 mil-m-38510 Fest Data Document: Bodo3-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: Wa Julit Of Measure: Demilitarization:	1.290 inches
Sody Height: 0.225 inches Departing Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in, mil-std-883, class a and monolithic nclosure Configuration: Flat pack Case Outline Source And Designator: Fly-02 mil-m-38510 Flest Data Document: 80063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing), such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing), such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80	Body Width:
Departing Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in, mil-std-883, class a and monolithic Inclosure Configuration: Flat pack Case Outline Source And Designator: Fly-02 mil-m-38510 Fest Data Document: B0063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Fig:	0.610 inches
Operating Tempurature Range: 55.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in, mil-std-883, class a and monolithic Inclosure Configuration: Flat pack Case Outline Source And Designator: Ty-02 mil-m-38510 Fest Data Document: Bio063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, arc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: W/a Juit Of Measure: - Demilitarization: No Fig:	Body Height:
55.0 to 125.0 degrees celsius Features Provided: Bipolar and burn in, mil-std-883, class a and monolithic noclosure Configuration: Flat pack Case Outline Source And Designator: Ty-02 mil-m-38510 Fest Data Document: Bio063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, atc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: No Demilitarization: No Figure Provided: Provided Standard Stan	0.225 inches
Features Provided: Sipolar and burn in, mil-std-883, class a and monolithic Inclosure Configuration: Flat pack Case Outline Source And Designator: Fly-02 mil-m-38510 Fest Data Document: 80063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Operating Tempurature Range:
Bipolar and burn in, mil-std-883, class a and monolithic nclosure Configuration: Flat pack Case Outline Source And Designator: Ty-02 mil-m-38510 Test Data Document: Biological and survey of the past of the pas	-55.0 to 125.0 degrees celsius
Inclosure Configuration: Flat pack Case Outline Source And Designator: Ty-02 mil-m-38510 Test Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Julit Of Measure: Demilitarization: No Fig:	Features Provided:
Case Outline Source And Designator: Ty-02 mil-m-38510 Fest Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing) and 80063-sm-a-813927 drawing (this	Bipolar and burn in, mil-std-883, class a and monolithic
Case Outline Source And Designator: Ty-02 mil-m-38510 Test Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inclosure Configuration:
Fest Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Flat pack
Fest Data Document: 30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No	Case Outline Source And Designator:
30063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ty-02 mil-m-38510
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	Test Data Document:
drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	80063-sm-a-838654 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Jnit Of Measure: Demilitarization: No Fig:	etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-838664
passic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any
Shelf Life: N/a Unit Of Measure: Cemilitarization: No Filig:	specification, standard or other document that may be referenced in a basic governing drawing) and 80063-sm-a-813927 drawing (this is the
Shelf Life: N/a Unit Of Measure:	basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification,
N/a Unit Of Measure: Demilitarization: No Fiig:	standard or other document that may be referenced in a basic governing drawing)
Jnit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Filg:	Unit Of Measure:
No Filg:	
Filg:	Demilitarization:
	No
	Fiig:
\ 458a0	A458a0