NSN 5962-01-149-2404

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-149-2404 **Body Length:** Between 0.750 inches and 0.785 inches **Body Width:** Between 0.245 inches and 0.271 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 670.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/resistor and positive outputs **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 36.0 volts power source **Test Data Document:** 12909-405561 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure:** Demilitarization: Yes - demil/mli