NSN 5962-01-149-7061

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-149-7061

Bodv	l er	nath:
Dogv		IMUI.

Between 0.745 inches and 0.785 inches

Body Width:

Between 0.240 inches and 0.260 inches

Body Height:

Between 0.135 inches and 0.150 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

6625-01-084-0207 test set, communication

Features Provided:

Hermetically sealed and monolithic and presettable and synchronous and cascadable and medium speed

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

9 input

Design Function And Quantity:

1 counter, binary coded decimal up/down

Case Outline Source And Designator:

Mo-001-ac joint electron device engineering council

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

20.0 volts power source

Time Rating Per Chacteristic:

15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level output

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

NSN 5962-01-149-7061Digital Microcircuit - Page 2 of 2



Fiig:

A458a0