NSN 5962-01-149-7703

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-149-7703

Bodv	l er	nath:
Douv	LCI	ıuıı.

Between 1.450 inches and 1.470 inches

Body Width:

Between 0.515 inches and 0.550 inches

Body Height:

Between 0.140 inches and 0.180 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Aircraft, harrier av-8b; velocity pool reparable piece parts; aircraft, hornet f/a-18

Features Provided:

Hermetically sealed and burn in and programmable and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

17 input

Criticality Code Justification:

Feat

Current Rating Per Characteristic:

140.00 milliamperes supply

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Capitance Rating Per Characteristic:

4.00 input picofarads and 7.00 output picofarads

Time Rating Per Chacteristic:

65.00 nanoseconds propagation delay time, low to high level output and 65.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Pal

Special Features:

Weapon system essential

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

NSN 5962-01-149-7703

Memory Microcircuit - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0