NSN 5962-01-150-3877

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-150-3877 **Body Length:** 0.760 inches **Body Width:** 0.248 inches **Body Height:** 0.135 inches **Maximum Power Dissipation Rating:** 27.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and negative outputs and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 multiplier, analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 40.0 volts power source **Time Rating Per Chacteristic:** 500.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 81755-c8982 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Yes - demil/mli Fiig:

Demilitarization:

A458a0