NSN 5962-01-150-6772

Digital Microcircuit - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-150-6772

view Offilite at https://aerobasegroup.com/nsii/0302-01-130-01/12
Body Length:
0.390 inches
Body Width:
Between 0.235 inches and 0.260 inches
Body Height:
Between 0.045 inches and 0.085 inches
Maximum Power Dissipation Rating:
100.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and burn in and hermetically sealed and dynamic and positive outputs
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Flat pack
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 inverter
Case Outline Source And Designator:
F-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.5 volts power source
Time Rating Per Chacteristic:
110.00 nanoseconds propagation delay time, low to high level output and 110.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
86360-515c5430-01 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
14 flat leads
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5962-01-150-6772

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0