## NSN 5962-01-150-8197

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-150-8197

## **Body Length:** 0.390 inches **Body Width:** Between 0.235 inches and 0.260 inches **Body Height:** Between 0.045 inches and 0.085 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+175.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed and burn in and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 gate, exclusive or **Case Outline Source And Designator:** F-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 270.00 nanoseconds propagation delay time, low to high level output and 270.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 86360-515c2030-03 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 14 flat leads Shelf Life: N/a Unit Of Measure:

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-150-8197

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

