## NSN 5962-01-151-1332

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-151-1332

Body Length:
Between 0.745 inches and 0.770 inches
Body Width:
Between 0.240 inches and 0.260 inches
Body Height:
Between 0.055 inches and 0.140 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
An/bqh- (v) 4 data gathering set
Features Provided:
Hermetically sealed and high voltage and w/inhibit and w/odd-even check
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
10 input
Design Function And Quantity:
1 generator, parity, checker
Case Outline Source And Designator:
Mo-001-ab joint electron device engineering council
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.5 volts power source
Time Rating Per Chacteristic:
700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low leve

## **Terminal Type And Quantity:**

14 printed circuit

Shelf Life:

N/a

output

Unit Of Measure:

Demilitarization:

Yes - demil/mli

## **NSN 5962-01-151-1332**Digital Microcircuit - Page 2 of 2



Fiig:

A458a0