NSN 5962-01-152-0032

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-152-0032

| View Online at https://aerobasegroup.com/nsn/5962-01-152-0032 |
|---|
| Body Length: |
| Between 1.230 inches and 1.285 inches |
| Body Width: |
| Between 0.510 inches and 0.545 inches |
| Body Height: |
| 0.225 inches |
| Maximum Power Dissipation Rating: |
| 2.0 watts |
| Operating Tempurature Range: |
| -40.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+125.0 degrees celsius |
| End Application: |
| 49200394143dq |
| Features Provided: |
| Hermetically sealed and burn in and programmable and positive outputs |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 10 input |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -20.0 volts power source |
| Time Rating Per Chacteristic: |
| 900.00 nanoseconds propagation delay time, low to high level output and 900.00 nanoseconds propagation delay time, high to low leve |
| output |
| Memory Device Type: |
| Rom |
| Memory Capacity: |
| Unknown |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 24 printed circuit |
| Shelf Life: |
| N/a |

--

Unit Of Measure:

NSN 5962-01-152-0032

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0