

View Online at <https://aerobasegroup.com/nsn/5962-01-152-0904>

Body Length:

Between 1.236 inches and 1.290 inches

Body Width:

0.560 inches

Body Height:

Between 0.130 inches and 0.170 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and programmed and 3-state output and bipolar

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

11 input

Current Rating Per Characteristic:

185.00 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Capitance Rating Per Characteristic:

5.00 input picofarads and 8.00 output picofarads

Time Rating Per Chacteristic:

90.00 nanoseconds access

Memory Device Type:

Prom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0