NSN 5962-01-152-6783

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-152-6783

View Online at https://aerobasegroup.com/nsn/5962-01-152-6783
Body Length:
Between 1.235 inches and 1.265 inches
Body Width:
Between 0.540 inches and 0.560 inches
Body Height:
Between 0.115 inches and 0.180 inches
Maximum Power Dissipation Rating:
440.0 milliwatts
Operating Tempurature Range:
-0.0/+70.0 degrees celsius
Storage Tempurature Range:
-55.0/+125.0 degrees celsius
Features Provided:
Static operation and 3-state output
Inclosure Material:
Plastic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
N-type metal oxide-semiconductor logic
Input Circuit Pattern:
15 input
Design Function And Quantity:
1 generator, character
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.3 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
350.00 nanoseconds propagation delay time, low to high level output
Hybrid Technology Type:
Monolithic
Test Data Document:
33214-139-358 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-152-6783

Hybrid Microcircuit - Page 2 of 2



Fiig:

A458a0