## NSN 5962-01-153-0177

Memory Microcircuit - Page 1 of 2

--



View Online at https://aerobasegroup.com/nsn/5962-01-153-0177

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
739.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and 3-state output and w/enable and programmable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
nput Circuit Pattern:
6 input
Case Outline Source And Designator:
D-2 mil-m-38510
Ferminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
1.5 volts power source and 5.5 volts power source
Time Rating Per Chacteristic:
80.00 nanoseconds propagation delay time, low to high level output and 80.00 nanoseconds propagation delay time, high to low le
putput
Memory Device Type:
Rom
Memory Capacity:
Unknown
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

## NSN 5962-01-153-0177

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

