## NSN 5962-01-154-1066

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-154-1066

## **Body Length:** 1.450 inches **Body Width:** 0.550 inches **Body Height:** 0.115 inches **Maximum Power Dissipation Rating:** 1192.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and monolithic and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 16 channel and 21 input **Design Function And Quantity:** 1 multiplexer **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 24.0 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Test Data Document:**

17863-7117598 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

## **Terminal Type And Quantity:**

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0