## NSN 5962-01-155-1507

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-155-1507

| Body Length:  |     |
|---|-----|
| 0.440 inches  |     |
| Body Width:   |     |
| Between 0.245 inches and 0.285 inches   |     |
| Body Height:  |     |
| Between 0.045 inches and 0.085 inches   |     |
| Maximum Power Dissipation Rating:   |     |
| 860.0 milliwatts  |     |
| Operating Tempurature Range:  |     |
| -55.0/+125.0 degrees celsius  |     |
| Storage Tempurature Range:  |     |
| -55.0/+150.0 degrees celsius  |     |
| Features Provided:  |     |
| Hermetically sealed and monolithic and w/clock  |     |
| Inclosure Material:   |     |
| Ceramic and glass   |     |
| Inclosure Configuration:  |     |
| Flat pack   |     |
| Output Logic Form:  |     |
| Emitter-coupled logic   |     |
| Input Circuit Pattern:  |     |
| 8 input   |     |
| Design Function And Quantity:   |     |
| 1 counter, universal  |     |
| Case Outline Source And Designator:   |     |
| F-5 mil-m-38510   |     |
| Terminal Surface Treatment:   |     |
| Solder  |     |
| Voltage Rating And Type Per Characteristic:   |     |
| 8.0 volts power source  |     |
| Time Rating Per Chacteristic:   |     |
| 11.00 nanoseconds propagation delay time, low to high level output and 11.00 nanoseconds propagation delay time, high to low level      |     |
| output  |     |
| Test Data Document:   |     |
| 97942-583r387 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc. | с.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |     |
| Terminal Type And Quantity:   |     |
| 16 flat leads   |     |
| Shelf Life:   |     |
| N/a   |     |
| Unit Of Measure:  |     |
|   |     |
| Demilitarization:   |     |
| No  |     |

No

## **NSN 5962-01-155-1507** Digital Microcircuit - Page 2 of 2

Fiig: A458a0

