

View Online at <https://aerobasegroup.com/nsn/5962-01-155-1510>

**Body Length:**

0.970 inches

**Body Width:**

Between 0.245 inches and 0.285 inches

**Body Height:**

Between 0.155 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

887.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and monolithic and 3-state output and high impedance

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

10 input

**Design Function And Quantity:**

8 buffer and 8 driver, line

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Time Rating Per Characteristic:**

10.50 nanoseconds propagation delay time, low to high level output and 10.50 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

97942-584r045 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0