## NSN 5962-01-155-4982

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-155-4982 **Body Length:** Between 0.375 inches and 0.395 inches **Body Width:** Between 0.245 inches and 0.265 inches **Body Height:** 0.125 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4920-01-064-0600 test console **Features Provided:** High impedance and high gain and bipolar and internally compensated and high slew rate and wideband **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 12.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli