NSN 5962-01-156-1550

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-156-1550 **Body Length:** 1.760 inches **Body Width:** 1.160 inches **Body Height:** 0.230 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -25.0 to 85.0 degrees celsius Storage Tempurature Range: -55.0 to 125.0 degrees celsius **End Application:** Radar set an/sps-49v1-3 **Features Provided:** Hermetically sealed and hybrid **Inclosure Material:** Metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 12 input **Design Function And Quantity:** 1 converter, analog to digital **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 6000.00 nanoseconds propagation delay time, low to high level output **Test Data Document:** 10001-2907259 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 32 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization: Yes - demil/mli

NSN 5962-01-156-1550

Digital-linear Microcircuit - Page 2 of 2



Fiig:

A458a0