NSN 5962-01-157-2810

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-157-2810

| Body Length: |
|--|
| Between 0.745 inches and 0.840 inches |
| Body Width: |
| Between 0.240 inches and 0.260 inches |
| Body Height: |
| 0.180 inches |
| Maximum Power Dissipation Rating: |
| 300.0 milliwatts |
| Operating Tempurature Range: |
| -40.0/+85.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| 5895-01-129-1827 central, communi |
| Features Provided: |
| Medium speed and w/buffered output and balanced and high fan-out |
| Inclosure Material: |
| Plastic |
| Inclosure Configuration: |
| Dual-in-line Dual-in-line |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 10 input |
| Design Function And Quantity: |
| 4 gate, and-or |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 18.5 volts power source |
| Time Rating Per Chacteristic: |
| 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level |
| output |
| Terminal Type And Quantity: |
| 16 printed circuit |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: A458a0