NSN 5962-01-158-1122

Linear Microcircuit - Page 1 of 1

Yes - demil/mli

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-158-1122 **Body Length:** Between 0.770 inches and 0.810 inches **Body Width:** Between 0.280 inches and 0.300 inches **Body Height:** Between 0.060 inches and 0.120 inches **Maximum Power Dissipation Rating:** 450.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and w/switch and burn in, mil-std-883, class b and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 4 input and 8 channel **Design Function And Quantity:** 1 multiplexer, analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 17.0 volts power source **Test Data Document:** 50027-9999-3348 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** Demilitarization: