## NSN 5962-01-158-2539

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-158-2539

Body Length:
2.096 inches
Body Width:
Between 0.510 inches and 0.620 inches
Body Height:
Between 0.165 inches and 0.205 inches
Maximum Power Dissipation Rating:
550.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and electrostatic sensitive
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
D-6 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
450.00 nanoseconds propagation delay time, low to high level output
Memory Device Type:
Ram
Memory Capacity:
Unknown
Test Data Document:
82577-932925 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
18 printed circuit
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5962-01-158-2539

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

