NSN 5962-01-159-3535

Linear Microcircuit - Page 1 of 2

Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-159-3535

view Offiline at https://aerobasegroup.com/hist//3302-01-133-3333
Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
0.210 inches
Maximum Power Dissipation Rating:
3.2 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5820-01-148-3976 radio terminal set
Features Provided:
Monolithic and low power and schottky and hermetically sealed and burn in
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
12 input
Design Function And Quantity:
4 transceiver
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
49956-954389 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.
excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

NSN 5962-01-159-3535

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0