## NSN 5962-01-159-3572

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-159-3572 **Body Length:** 1.460 inches **Body Width:** 0.520 inches **Body Height:** 0.170 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -20.0/+70.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius **End Application:** Communication set, type an/grc-212 **Features Provided:** Hermetically sealed and high power and monolithic **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 1 driver, light-emitting diode **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 6.3 volts power source **Time Rating Per Chacteristic:** 400.00 nanoseconds propagation delay time, low to high level output and 400.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-159-3572

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0