# NSN 5962-01-159-6866

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-159-6866

## **Body Length:**

Between 0.935 inches and 1.000 inches

# Body Width:

Between 0.245 inches and 0.310 inches

# **Body Height:**

0.220 inches

**Maximum Power Dissipation Rating:** 

605.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### End Application:

Radio terminal, type an/trc-170

#### **Features Provided:**

Hermetically sealed and monolithic and low power and schottky and w/enable and w/clock

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

## Input Circuit Pattern:

12 input

#### **Design Function And Quantity:**

4 transceiver

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

5.5 volts power source

#### Time Rating Per Chacteristic:

40.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

49956-954066 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

#### Terminal Type And Quantity:

20 printed circuit

Shelf Life:

N/a

# Unit Of Measure:

--

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0