## NSN 5962-01-159-6868

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-159-6868

| Body Length:   |
|--|
| 0.840 inches   |
| Body Width:  |
| Between 0.220 inches and 0.310 inches  |
| Body Height:   |
| 0.185 inches   |
| Maximum Power Dissipation Rating:  |
| 500.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| End Application:   |
| 5820-01-148-3976 radio terminal set  |
| Features Provided:   |
| Monolithic and hermetically sealed and w/field effect transistor switch  |
| Inclosure Material:  |
| Ceramic and glass  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Input Circuit Pattern:   |
| 8 channel  |
| Design Function And Quantity:  |
| 1 multiplexer, eight to one line   |
| Case Outline Source And Designator:  |
| D-2 mil-m-38510  |
| Terminal Surface Treatment:  |
| Tin  |
| Voltage Rating And Type Per Characteristic:  |
| 15.0 volts power source  |
| Test Data Document:  |
| 49956-g166757 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                              |
| Terminal Type And Quantity:  |
| 16 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A458a0   |
|  |