## NSN 5962-01-159-7868

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-159-7868 **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and hermetically sealed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** D-4 mil-m-38510 **Current Rating Per Characteristic:** 5.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -22.0 volts power source and 22.0 volts power source **Special Features:** Ultra low offset **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

## NSN 5962-01-159-7868

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0