NSN 5962-01-159-7878



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-159-7878 **Body Length:** Between 1.150 inches and 1.250 inches **Body Width:** Between 0.580 inches and 0.610 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** An/usm-464 test set, countermeasures **Features Provided:** Monolithic and static operation and w/enable and w/buffered output and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 22 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 6.0 volts power source **Memory Device Type:** Ram **Memory Capacity:** Unknown

Test Data Document:

94117-314076 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-159-7878

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0