NSN 5962-01-160-3250

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-160-3250

Overall Height:

0.330 inches

Body Length:

Between 0.755 inches and 0.785 inches

Body Width:

Between 0.245 inches and 0.280 inches

Body Height:

0.180 inches

Maximum Power Dissipation Rating:

45.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and low power and schottky

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

4 input

Design Function And Quantity:

1 counter, divide by two and six

Case Outline Source And Designator:

To-116 joint electron device engineering council

Time Rating Per Chacteristic:

48.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0