NSN 5962-01-160-7082



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-160-7082 **Body Length:** Between 0.815 inches and 0.840 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** 0.160 inches **Maximum Power Dissipation Rating:** 360.0 milliwatts **Operating Tempurature Range:** -30.0/+85.0 degrees celsius Storage Tempurature Range: -55.0/+125.0 degrees celsius **Features Provided:** Schottky and w/totem pole output and high speed and negative outputs **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Emitter-coupled logic **Input Circuit Pattern:** Quad 2 input **Design Function And Quantity:** 4 translator, ecl to ttl **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 8.0 volts power source **Time Rating Per Chacteristic:** 6.00 nanoseconds propagation delay time, low to high level output and 6.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0