## NSN 5962-01-160-7134

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-160-7134

De de Leurette	
Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inches and	10.310 Inches
Body Height:	
Between 0.140 inches and	
Maximum Power Dissipa	ition Rating:
739.0 milliwatts	
Operating Tempurature	
-55.0/+125.0 degrees cels	
Storage Tempurature Ra	
-65.0/+150.0 degrees cels	lus
End Application:	
Radar system, type an/fps	;-117
Features Provided:	
	nonolithic and bipolar and programmable and schottky
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
10 input	
Case Outline Source And	d Designator:
D-2 mil-m-38510	
Terminal Surface Treatm	ient:
Solder	
Voltage Rating And Type	e Per Characteristic:
5.5 volts power source	
Time Rating Per Chacter	istic:
75.00 nanoseconds propa	agation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level
output	
Memory Device Type:	
Rom	
Memory Capacity:	
Unknown	
Terminal Type And Quar	ntity:
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	

---

## NSN 5962-01-160-7134

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

