## NSN 5962-01-160-7737

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-160-7737

Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inche	s and 0.310 inches
Body Height:	
0.185 inches	
Maximum Power Di	ssipation Rating:
739.0 milliwatts	
Operating Tempura	ture Range:
-55.0/+125.0 degree	s celsius
Storage Tempuratu	re Range:
-65.0/+150.0 degree	s celsius
End Application:	
An/fps-117 radar sys	tem
Features Provided:	
Hermetically sealed	and burn in and bipolar and schottky and programmable and w/enable and w/active pull-up
Inclosure Material:	
Ceramic	
Inclosure Configura	ation:
Dual-in-line	
Output Logic Form	
Transistor-transistor	logic
Input Circuit Patter	n:
10 input	
Case Outline Sourc	e And Designator:
D-2 mil-m-38510	
Terminal Surface T	reatment:
Solder	
Voltage Rating And	Type Per Characteristic:
5.5 volts power sou	ce
Time Rating Per Ch	acteristic:
75.00 nanoseconds	propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low level
output	
Memory Device Typ	ie:
Rom	
Memory Capacity:	
Unknown	
Terminal Type And	Quantity:
16 printed circuit	
Shelf Life:	
N/a	
Unit Of Measure:	

## NSN 5962-01-160-7737

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

