## NSN 5962-01-161-3478

Memory Microcircuit - Page 1 of 2

---



View Online at https://aerobasegroup.com/nsn/5962-01-161-3478

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
739.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
End Application:
Radar system, type an/fps-117
Features Provided:
Hermetically sealed and monolithic and high impedance and 3-state output and programmable and bipolar
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
10 input
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
5.5 volts power source
Time Rating Per Chacteristic:
75.00 nanoseconds propagation delay time, low to high level output and 75.00 nanoseconds propagation delay time, high to low leve
output
Memory Device Type:
Rom
Memory Capacity:
Unknown
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:

## NSN 5962-01-161-3478

Memory Microcircuit - Page 2 of 2

## Demilitarization:

Yes - demil/mli

Fiig:

A458a0

